

| Wheel Dia. | Tread Width.                  | Overall Height    | Offset             | Wheel Type   | Socket Fitting           |                                | Spring Loaded Solid Plug Fitting  |                                |  |
|------------|-------------------------------|-------------------|--------------------|--|--------------------------|--------------------------------|---|--------------------------------|--|
| A          | B                             | C                 | D                  |  | Dynamic Capacity In Kgs. | Static Capacity S.W.L. In Kgs. | Catalog Reference   | Static Capacity S.W.L. In Kgs. | Catalog Reference  |
| 150 (6")   | 44.5 (1 1/2 3/4;")<br>50 (2") | 197 (7 1/2 3/4;") | 44.5 (1 1/2 3/4;") | Rubber Tyred (RT) Cast Iron (C) Nylon (N) Phenorex (P) | 370<br>410<br>410<br>410 | 820                            | RD5 /SCF2 /RT /150<br>RD5 /SCF2 /C /150RD5 /SCF2 /N /150RD5 /SCF2 /P /150 | 820                            | RD5 /SPS1 /RT /150 RD5 /SPS1 /C /150<br>RD5 /SPS1 /N /150RD5 /SPS1 /P /150 |
| 200 (8")   | 50 (2")                       | 243 (9 9 /16")    | 44.5 (1 1/2 3/4;") | Rubber Tyred (RT) Cast Iron (C)                        | 500                      | 820                            | RD5 /SCF2 /RT /200<br>RD5 /SCF2 /C /200                                   | 820                            | RD5 /SPS1 /RT /200<br>RD5 /SPS1 /C /200                                    |
|            |                               |                   |                    | Nylon (N) Phenorex (P)                                 |                          |                                | RD5 /SCF 2 /N /200<br>RD5 /SCF2 /P /200                                   |                                | RD5 /SPS 1 /N /200<br>RD5 /SPS1 /P /200                                    |